

SlimLine 68 Windows



Reynaers SL 68 window has been designed specifically to meet the needs of UK households. This unique and expertly engineered window suite offers the discerning homeowner the perfect combination of exceptionally slim frames and the highest levels of performance. With sleek, clean lines, these beautifully designed windows can transform the appearance of any home,

adding value to the property whilst also making it warmer, brighter and more secure.

Perfectly complementing both contemporary and traditional styles of property, the SL 68 window is stylish and timeless in its design.



Reynaers
at Home

www.reynaersathome.co.uk

Warm and cosy

One of the most noticeable differences for many homeowners is how warm and cosy their home feels once their new windows and doors are in place. The SL 68 is designed to offer class-leading insulation levels without compromising on the appearance of the window. The result is a window that will keep heat loss through the window to a minimum, withstand the worst that the British weather has to throw at it, and will help keep your energy bills down.

- Industry-leading thermal insulation
- Double and triple glazed options
- Unique thermal insulation profiles
- U-value as low as 1.1 W/m²K
- Window energy rating up to A

Safe and secure

Reynaers SL 68 window is designed and tested to the most stringent security standards. Knowing that this window has been awarded the Secured by Design accreditation means you can rest assured that your home, your family and your prized possessions are as safe as can be from would-be intruders.

- One of the most secure windows available
- PAS24
- Secured by Design
- Enhanced security with hinge-side security brackets
- Multi-point locking mechanism
- Lockable handle

Peace and quiet

Not only is the frame of the SL 68 window designed to help eliminate unwanted noise, the system is also flexible enough to allow a glazed unit up to 43 mm thick to be specified. This makes it possible to incorporate fairly sophisticated acoustic glazing, which makes a huge difference if you live near a busy road, a railway or an airport.



Tried and tested

The SL 68 window was designed by a highly experienced team of engineers at Reynaers' purpose-built, world-class design and testing facility. As with all Reynaers products, this window has been put through the most stringent test regime, ensuring that it is one of the highest-performing and most reliable windows available.

- Premium quality materials
- Highest levels of performance
- Industry-leading weather resistance

As individual as you are

All Reynaers windows and doors are made to meet your exact requirements. From the design of the window to the colour of the frame and handle, there are almost unlimited options. When you choose Reynaers, you can make your windows and doors truly individual, a design statement to be proud of.

- Huge range of design options
- Hundreds of colour options
- Different colour inside and out
- Compatible with trickle ventilation*








*Installer supplied

- Choice of handles

Technical characteristics

Design variant		Functional
Min. visible width outward-opening window	Frame + Vent	65mm
Min. visible width T-profile		56mm
Overall system depth window	Frame	68mm
	Vent	68mm
Rebate height		18mm
Glass thickness		up to 43 mm
Glazing method		dry glazing with EPDM or neutral silicones
Thermal insulation		omega-shaped fibreglass reinforced polyamide strips (32 mm)
High Insulation variant (HI)		available

Performances

Energy											
 Thermal insulation ⁽¹⁾ EN 10077-2	Uw ≥1.1 W/m²K with TGU Uw ≥1.4 W/m²K with DGU										
Comfort											
 Acoustic performance ⁽²⁾ EN ISO 140-3; EN ISO 717-1	Rw (C; Ctr) = 36 (-1; -5) dB / 47 (-2; -7) dB, depending on glazing type										
 Air-tightness, max. test pressure ⁽⁴⁾ EN 1026; EN 12207	1 (150 Pa)		2 (300 Pa)			3 (600 Pa)			4 (600 Pa)		
 Water-tightness ⁽⁵⁾ EN 1027; EN 12208	1A (0 Pa)	2A (50 Pa)	3A (100 Pa)	4A (150 Pa)	5A (200 Pa)	6A (250 Pa)	7A (300 Pa)	8A (450 Pa)	9A (600 Pa)	E1050 (>1050 Pa)	
 Wind load resistance, max. test pressure ⁽⁵⁾ EN 12211; EN 12210	1 (400 Pa)		2 (800 Pa)		3 (1200 Pa)		4 (1600 Pa)		5 (2000 Pa)		
 Wind load resistance to frame deflection ⁽⁶⁾ EN 12211; EN 12210	A (≤ 1/150)			B (≤ 1/200)				C (≤ 1/300)			
Safety											
 Burglar resistance ⁽⁷⁾ ENV 1627 - ENV 1630, UK SBD PASS	PAS 24:2016 SBD accredited										

This table shows possible classes and values of performances. The values indicated in grey are the ones relevant to this system.

⁽¹⁾ Window dimension 1.23m x 1.48m, side hung next to fixed, with TGU of 0.7 W/m²K or DGU of 1.0 W/m²

⁽²⁾ The sound reduction index (Rw) measures the capacity of the sound reduction performance of the frame.

⁽³⁾ The air tightness test measures the volume of air that would pass through a closed window at a certain air pressure.

⁽⁴⁾ The water tightness testing involves applying a uniform water spray at increasing air pressure until water penetrates the window.

⁽⁵⁾ The wind load resistance is a measure of the profile's structural strength and is tested by applying increasing levels of air pressure to simulate the wind force. There are up to five levels of wind resistance (1 to 5) and three deflection classes (A,B,C). The higher the number, the better the performance.

⁽⁶⁾ The burglar resistance is tested by static and dynamic loads, as well as by simulated attempts to break in using specified tools. This variant requires specific burglar resistance

Partner details



Our partners

Reynaers at Home connects you to a network of carefully selected Partners who will guide you through your home transformation process, from the initial design and specification stages through to the supply and installation of your bespoke aluminium window and door systems.

For more information, please visit www.reynaersathome.co.uk

Why Reynaers?

For over 50 years, Reynaers Aluminium Ltd has been designing cutting-edge glazing solutions for some of the most iconic buildings in the world.

Engineered without compromise, our ranges of aluminium windows, doors and curtain wall systems have been specified time and again by the world's leading architects and construction companies.



**Reynaers
Aluminium**

**Windows.
Doors.
Conservatories.**

Together for better